

Hoses with design factor >2:1
2244N







2244N – High pressure hose



CONSTRUCTION

Core tube : Polyamide
Pressure reinforcement : Two spiral layers, one braided layer of high tensile steel wire
Cover : Polyurethane
Standard colour : Black


TEMPERATURE RANGE -10°C up to +70°C

#											
	DN	size	mm	inch	mm	MPa	psi	MPa	psi	mm	kg/m
2244N-06V10W	10	-06	9.7	3/8	18.0	86	12,470	215	31,175	120	0.50
2244N-08V10W	12	-08	12.8	1/2	22.7	88	12,760	220	31,900	150	0.80





NOTES –

Αριθμός (06/08/10) που βρίσκεται στο άκρο της γάντζας


1C9KX / 1C9LX – Metric female swivel heavy series with O-ring







MATERIAL Special materials

#						A	B				Nipple ID	Ferrule OD
	DN	size	mm	inch					mm	MPa		
1C9KX-14-06W	10	-06	9.5	3/8	M22x1.5	79	37	27	86	12,470	7.0	23.5
1C9LX-16-08	12	-08	12.7	1/2	M24x1.5	88	34	30	130	18,850	6.8	30.0

192KX / 192LX – BSP female swivel (60° cone)




MATERIAL Special materials





#						A	B				Nipple ID	Ferrule OD
	DN	size	mm	inch					MPa	psi		
192KX-6-06W	10	-06	9.5	3/8	G3/8	72	29	22	86	12,470	7.0	23.5
192LX-8-08W	12	-08	12.7	1/2	G1/2	75	21	30	130	18,850	6.7	30.7

Hoses with design factor >2:1
1AYKX / 1AYLX

1AYKX / 1AYLX – Type “M” female swivel



MATERIAL Special materials

#						A	B				Nipple ID	Ferrule OD
	DN	size	mm	inch		mm	mm		MPa	psi		
1AYKX-8-06W	10	-06	9.5	3/8	3/4 - 16UNF	74	32	27	86	12,470	7.0	23.5
1AYLX-11-08	12	-08	12.7	1/2	1 - 12 UNF	80	27	32	130	18,850	6.7	30.7

Design Factor >2:1

ΑΕΡΕΩΣΗ ΜΕΤΑΦΟΡΑ (ΟΥΔΕΝΩΣΗ) ΟΥΔΕΝΩΣΗ ΣΕ ΤΥΠΟΤΑΧΥ ΠΛΩΜΕΝΟ ΤΥΠΩΣΗ