


OIL-HYDRAULIC PISTON PUMP IRON CAST BENT AXIS PUMP



	Main Data			
Pumps BIF	50M			
Displacement (cm ³ /rot.)	50			
Operating pressure (bar) (up to)	400			
Peak pressure (bar)	450			
Operating rotation ¹ (rpm)	2300			
Max. rotation without load ¹ (rpm)	3000			
Weight (approx.) (kg)	12.3			
Pistons quantity				
A-Oil outlet (DIN ISO 228)	3/4"BSP			
B-Oil inlet (DIN ISO 228)	1"BSP			
С	Drain hole			


How to order:

Example: Pump 50cm³/rot; operating pressure up to 400 bar; peak pressure 450 bar, ref. BIF M BIF50M

Fluids	mineral oils type ISO HM or DIN 51524-2 HLP
Recommended viscosity range	20 to 40 cSt (mm2/s) at working temperature
Limits viscosity range	10 to 750 cSt (mm2/s)
Start-up viscosity range, without load	750 to 1500 cSt (mm2/s)
Filtration	10μm ISO4406 18/13
Inlet pressure range	0,7 to 2 bar abs
In the application of any of these pumps; the use of these data does not exempt the reading of the instru	uction "BI pumps rec ommendations before start-up"



OIL-HYDRAULIC PISTON PUMP IRON CAST BENT AXIS PUMP



Hose dimensions

Inlet Hose				
Flow (I/min)	Internal pipe diameter (inch)			
20-30	1"1/4			
30-40	1"1/4			
50-60	1"1/2			
70-90	1"3/4			
100-120	2"			

Outlet Hose						
Flow (I/min)	Internal pipe diameter (inch)					
20	1/2"	1/2"	1/2"	1/2"	1/2"	
30	1/2"	1/2"	1/2"	1/2"	1/2"	
40	5/8"	1/2"	1/2"	1/2"	1/2"	
50	5/8"	5/8"	5/8"	1/2"	1/2"	
60	3/4"	5/8"	5/8"	5/8"	5/8"	
70	1"	3/4"	3/4"	5/8"	5/8"	
80	1"	3/4"	3/4"	3/4"	3/4"	
90	1"	1"	1"	3/4"	3/4"	
100	1"	1"	1"	1"	3/4"	
110	1"	1"	1"	1"	1"	
	50-100	100-150	150-200	200-300	300-350	
	P (bar)					

Important notes:

- -To install one of these pumps, please consult and respect the instruction "BI pumps recommendations before start-up";
- Other axis available, please consult "Axel options".