


DADOS TECNICOS:



- 40 °C + 80 °C

Nota: temperatura máxima de funcionamento com líquidos que contenham água 65 °C.

*Vendido em rolos de 25, 50 e 100 m



100955								
CÓDIGO	mm	mm	mm	RAIO C mm	PRESSÃO bar	RUTURA bar	COMPRIMEN TO m	COR
TB.10.0302/BR	3	2	0.50	10	27	80	100	○
TB.10.0402/AZ	4	2	1.00	16	44	132	100	●
TB.10.0402/BR	4	2	1.00	16	44	132	100	○
TB.10.0402/PT	4	2	1.00	16	44	132	100	●
TB.10.0403/BR	4	3	0.5	16	33	100	100	○
TB.10.0503/AZ	5	3	1.00	20	33	100	100	●
TB.10.0503/BR	5	3	1.00	20	33	100	100	○
TB.10.0503/PT	5	3	1.00	20	33	100	100	●
TB.10.0603/PT	6	3	1.50	25	44	132	100	●
TB.10.0604/AZ	6	4	1.00	30	28	84	100	●
TB.10.0604/BR	6	4	1.00	30	28	84	100	○
TB.10.0604/PT	6	4	1.00	30	28	84	100	●
TB.10.0604/VM	6	4	1.00	30	28	84	100	●
TB.10.0805/PT	8	5	1.50	35	32	96	100	●
TB.10.0806/AM	8	6	1.00	40	20	60	100	●
TB.10.0806/AZ	8	6	1.00	40	20	60	100	●
TB.10.0806/BR	8	6	1.00	40	20	60	100	○
TB.10.0806/PT	8	6	1.00	40	20	60	100	●
TB.10.0806/VD	8	6	1.00	40	20	60	100	●
TB.10.0806/VM	8	6	1.00	40	20	60	100	●
TB.10.0906/PT	9	6	1.50	45	28	84	100	●
TB.10.1007/PT	10	7	1.50	58	23	70	50	●
TB.10.1008/AZ	10	8	1.00	60	16	48	50	●
TB.10.1008/BR	10	8	1.00	60	16	48	50	○
TB.10.1008/PT	10	8	1.00	60	16	48	50	●
TB.10.1008/VM	10	8	1.00	60	16	48	50	●
TB.10.1108/PT	11	8	1.50	60	21	64	50	●
TB.10.1209/BR	12	9	1.50	60	20	60	50	○
TB.10.1209/PT	12	9	1.50	60	20	60	50	●
TB.10.1210/AZ	12	10	1.00	85	12	36	50	●
TB.10.1210/BR	12	10	1.00	85	12	36	50	○
TB.10.1210/PT	12	10	1.00	85	12	36	50	●
TB.10.1410/PT	14	10	2.00	75	23	68	50	●
TB.10.1411/BR	14	11	1.50	85	16	48	50	○
TB.10.1411/PT	14	11	1.50	85	16	48	50	●
TB.10.1512/PT	15	12	1.50	90	16	48	50	●

100955								
CÓDIGO	mm	mm	mm	RAIO C mm	PRESSÃO bar	RUTURA bar	COMPRIMENTO m	COR
TB.10.1612/PT	16	12	2.00	95	20	60	50	●
TB.10.1613/PT	16	13	1.50	110	13	40	50	●
TB.10.1814/PT	18	14	2.00	100	17	52	50	●
TB.10.1815/PT	18	15	1.50	140	12	36	50	●
TB.10.2218/PT	22	18	2.00	200	13	39	50	●