

Composição: Interior em borracha EPDM, reforçado com telas têxteis sintéticas.

Propriedades: Resistente ao calor, envelhecimento e agentes atmosféricos.

Aplicação: Designado para sistemas de refrigeração de motores.

 -30 °C +120 °C



100952			
CÓDIGO	D (mm)	mm	L (mm)
TBI.455.10/200	10	4,5	200
TBI.455.13/200	13	4,5	200
TBI.455.16/200	16	4,5	200
TBI.455.18/200	18	4,5	200
TBI.455.20/200	20	4,5	200
TBI.455.22/200	22	4,5	200
TBI.455.25/200	25	4,5	200
TBI.455.28/200	28	4,5	200
TBI.455.30/200	30	4,5	200
TBI.455.32/200	32	4,5	200
TBI.455.35/200	35	4,5	200
TBI.455.38/200	38	4,5	200
TBI.455.40/200	40	4,5	200
TBI.455.42/200	42	4,5	200
TBI.455.45/200	45	4,5	200
TBI.455.48/200	48	4,5	200
TBI.455.50/200	50	4,5	200
TBI.455.55/200	55	4,5	200
TBI.455.60/200	60	4,5	200
TBI.455.65/200	65	4,5	200
TBI.455.70/200	70	4,5	200
TBI.455.76/200	76	4,5	200
TBI.455.80/200	80	4,5	200
TBI.455.90/250	90	4,5	250
TBI.455.100/250	100	4,5	250

